

MERCURY

PUSH LOCK HOSE



APPLICATIONS

Compressed air hose for low-pressure hydraulic and pneumatic systems, automation, maintenance, air and water, and general industries. Adaptable with push lock fittings for 300psi application.

TECHNICAL DESCRIPTION

Tube: Black, smooth, NBR rubber

Reinforcement: High strength synthetic cord

Cover: Smooth, synthetic rubber, oil, ozone, aging resistant. Black, red, yellow, blue, and green colors are available

Temperature Range: -40°C (-40°F) to +100°C (+212°F)

No.	Size (inch)	I.D. (mm)	O.D. (mm)	W.P.		B.P.		MBR (mm)	Weight (kg/m)	Length (m)
MERCURY-0025	1/4"	6.4	12.7	20	300	80	1200	65	0.13	100
MERCURY-0038	3/8"	9.5	15.9	20	300	80	1200	75	0.16	100
MERCURY-0050	1/2"	12.7	19.8	20	300	80	1200	130	0.27	100
MERCURY-0063	5/8"	15.9	23.0	20	300	80	1200	150	0.28	100
MERCURY-0075	3/4"	19.1	26.2	20	300	80	1200	180	0.36	80
MERCURY-0100	1"	25.4	32.5	20	300	80	1200	250	0.55	60

Dimensional tolerance is compliant with ISO 1307.