

APOLLO

EPDM MULTIPUROPSE AIR & WATER HOSE



APPLICATIONS

Softwall hose for general industries. Designed for delivery of air, water, and glycols-based antifreeze. Not recommended for chemicals or abrasion medium. EPDM rubber tube.

TECHNICAL DESCRIPTION

Tube: Black, smooth, insulating, EPDM synthetic rubber

Reinforcement: High strength synthetic cord

Cover: EPDM synthetic rubber, abrasion resistant. 3/16" - 1" is smooth, 1-1/4" - 2" is wrapped finish. Black, red, yellow, blue, and green colors are available

Temperature Range: -40°C (-40°F) to +100°C (+212°F)

No.	Size (inch)	I.D. (mm)	O.D. (mm)	W.P.		B.P.		Weight (kg/m)	Length (m)
APOLLO 10-0019	3/16"	4.8	12.0	10	150	30	450	0.10	100
APOLLO 10-0025	1/4"	6.4	13.0	10	150	30	450	0.12	100
APOLLO 10-0031	5/16"	7.9	15.0	10	150	30	450	0.16	100
APOLLO 10-0038	3/8"	9.5	17.0	10	150	30	450	0.20	100
APOLLO 10-0050	1/2"	12.7	21.0	10	150	30	450	0.26	100
APOLLO 10-0063	5/8"	15.9	26.0	10	150	30	450	0.35	100
APOLLO 10-0075	3/4"	19.1	29.0	10	150	30	450	0.36	80
APOLLO 10-0100	1"	25.4	36.0	10	150	30	450	0.59	60
APOLLO 10-0125	1-1/4"	31.8	44.0	10	150	30	450	0.98	40
APOLLO 10-0150	1-1/2"	38.1	54.0	10	150	30	450	1.20	40
APOLLO 10-0200	2"	50.8	66.0	10	150	30	450	1.66	40

No.	Size (inch)	I.D. (mm)	O.D. (mm)	W.P.		B.P.		Weight (kg/m)	Length (m)
APOLLO 20-0019	3/16"	4.8	12.0	20	300	60	900	0.12	100
APOLLO 20-0025	1/4"	6.4	13.0	20	300	60	900	0.14	100
APOLLO 20-0031	5/16"	7.9	15.0	20	300	60	900	0.18	100
APOLLO 20-0038	3/8"	9.5	17.0	20	300	60	900	0.22	100
APOLLO 20-0050	1/2"	12.7	21.0	20	300	60	900	0.31	100
APOLLO 20-0063	5/8"	15.9	26.0	20	300	60	900	0.45	100
APOLLO 20-0075	3/4"	19.1	29.0	20	300	60	900	0.53	80
APOLLO 20-0100	1"	25.4	36.0	20	300	60	900	0.73	60
APOLLO 20-0125	1-1/4"	31.8	44.0	20	300	60	900	1.12	40
APOLLO 20-0150	1-1/2"	38.1	54.0	20	300	60	900	1.32	40
APOLLO 20-0200	2"	50.8	66.0	20	300	60	900	1.78	40