

DIONE HT

STEAM CLEANING HOSE



STANDARDS



APPLICATIONS

Softwall steam cleaning hose. Designed for delivery of hot water and steam up to 165°C, nonfatty foodstuffs. Widely used for dairy, creamery, brewery, and beverage industries.

ADVANTAGES

Saturated steam resistance maximum to 165°C (329°F)

TECHNICAL DESCRIPTION

Tube: White, food-grade, smooth EPDM rubber. Phthalates free

Reinforcement: High strength synthetic textile

Cover: Blue EPDM rubber, smooth, ozone resistant

Temperature Range: -40°C (-40°F) to +120°C (+248°F)

* Saturated steam: maximum to 165°C (329°F)

No.	Size (inch)	I.D. (mm)	O.D. (mm)	W.P. (Water) (bar)	W.P. (Steam) (bar)	B.P. (bar) (psi)		MBR (mm)	Weight (kg/m)	Length (m)
DIONE HT-0050	1/2"	12.7	23.0	20	6	60	900	70	0.39	100
DIONE HT-0063	5/8"	15.9	27.0	20	6	60	900	90	0.45	100
DIONE HT-0075	3/4"	19.1	31.0	20	6	60	900	110	0.65	80
DIONE HT-0100	1"	25.4	37.0	20	6	60	900	130	0.81	60

Dimensional tolerance is compliant with ISO 1307.